

IN THE SPECIFICATION

The second full paragraph on page 1 has been amended as follows:

A typical conventional woodwork drill bit described in the Japanese Patent Application Laid-Open (Kokai) No. 2002-210708 ~~2002-21708~~ has a raked blade at the tip of a single spiral lead and a scribing blade that sticks out at the position opposite to the diameter direction of the raked blade. The applicant of the present invention has also developed a special woodwork drill bit to be used with a mechanical feeding means as described in the Japanese Utility Model Application Laid-Open (Kokai) No. H6-50162. This drill bit has two leads formed on it, and a cutting blade is established at the tip of each lead.

BEST AVAILABLE COPY

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.